



SV VP Series C2.6

| | |
|-------------------------------|--|
| LED Color | RGB |
| LED Spacing | 2.6mm |
| Pixel Density | 147,456 pix/m ² |
| Max Brightness | 1,200 nits |
| LED Type | Black Flip Chip SMD 1515 |
| Cabinet Size | 500mm × 500mm × 88mm D |
| Cabinet Resolution | 192 × 192 |
| Viewing Angle | 160° H × 160° V |
| Contrast Ratio | 8800 : 1 |
| LED Lifespan | 100,000 hours |
| IP Rating (Front/Rear) | IP40/IP21 |
| Operating Temp | -20°C to +50°C |
| Operating Humidity | 10% to 90% RH |
| Processor | Megapixel |
| Color Processing | 16 bit / color |
| Driver Scan Rate | 1/8 |
| System Ctrl Protocol | eDVI over Fiber |
| Dimming | Linear or Log 0-100% |
| Power Consumption | 680 W/m ² max, 230 W/m ² |
| Voltage Input | 100-240 VAC |
| Refresh Rate | 7680 Hz |
| Cabinet Weight | 35 kg/m ² |
| Material | Aluminum |
| Product Type | Hanging/stacking |
| Maintenance | Rear |
| Rear | 2 years |

SV VP Series M2.5

| | |
|-------------------------------|--|
| LED Color | RGB |
| LED Spacing | 2.5mm |
| Pixel Density | 160,000 pix/m ² |
| Max Brightness | 1,800 nits |
| LED Type | Black Flip Chip SMD 1515 |
| Cabinet Size | 500mm × 500mm × 88mm D |
| Cabinet Resolution | 200 × 200 |
| Viewing Angle | 160° H × 160° V |
| Contrast Ratio | 8800 : 1 |
| LED Lifespan | 100,000 hours |
| IP Rating (Front/Rear) | IP40/IP21 |
| Operating Temp | -20°C to +50°C |
| Operating Humidity | 10% to 90% RH |
| Processor | Megapixel |
| Color Processing | 16 bit / color |
| Driver Scan Rate | 1/8 |
| System Ctrl Protocol | eDVI over Fiber |
| Dimming | Linear or Log 0-100% |
| Power Consumption | 680 W/m ² max, 230 W/m ² |
| Voltage Input | 100-240 VAC |
| Refresh Rate | 7680 Hz |
| Cabinet Weight | 35 kg/m ² |
| Material | Aluminum |
| Product Type | Hanging/stacking |
| Maintenance | Rear |
| Rear | 2 years |

WORLD CLASS FIRM IN ADVANCED ENGINEERING + PERFORMANCE SPACE

